

Model: PB3N250B2EL

Motor: BE92EC

◆ 1.General Characters


1-1	Rated Voltage	230 VAC
1-2	Frequency	50/60 Hz
1-3	Operating Voltage	184~276 VAC
1-4	Rated Speed	2760 RPM
1-5	Input Current	0.9 A
1-6	Input Power	123 W
1-7	Air Flow	759.17 CFM / 1290 m ³ /H
1-8	Static Pressure	2.76 inH ₂ O / 690 Pa
1-9	Acoustical Noise	71 dB(A)
1-10	Life Expectance	50,000 Hours(L10) At 40°C room, humidity 15%~65%RH.
1-11	Insulation Class	Class B
1-13	Motor Protection	Locked rotor protection Polarity protection Automatic restart capability
1-14	Speed Control	Control input 0~10VDC / PWM
1-15	Protection Type	IP44
1-17	Signal Output	FG (Frequency Generator)

Model: PB3N250B2EL**Motor: BE92EC****◆ 2. Mechanical Characters**

2-1	Dimension	Ø250mm X 111.5mm (see dimension drawing)
2-2	Material of Impeller	PA6+GF
2-3	Number of Blades	11
2-4	Bearing System	NMB ball bearing
2-5	Lead Wire	AC(AWG20#), DC(AWG22 #)

◆ 3. Environmental Characters

3-1	Operating Temperature	-25°C to 60°C
3-2	Storage Temperature	-40°C to 75°C
3-3	Operating Humidity	5% to 90% RH
3-4	Storage Humidity	5% to 95% RH

Model: PB3N250B2EL**Motor: BE92EC****◆ 4. Performance Curve****Testing Condition**

Input Voltage----Operating voltage (230VAC/50Hz)

Temperature-----Room temperature

Humidity-----65%RH

